



NTN BEARING USA CORP.

1.25 Inch | 31.75 Millimeter x 2.012 Inch | 51.105 Millimeter x 1.813 Inch | 46.05 Millimeter skf P2BL 104-WF Ball bearing plummer block units



P2BL 104-WF Bearing 2D drawings and 3D CAD models

Bearing No. P2BL 104-WF

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.59
EAN	7316577345899
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	YEL 207-104-2F
Seals	Single Lip Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Flinger Seal
Long Description	2 Bolt Pillow Block; 1-1/4" Bore; 1-13/16" Base to Center Height; Eccentric Collar Mount; Ball Bearing; Relubricatable; Cast Iron; Single Lip Contact; Non-



NTN BEARING USA CORP.

	expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Weight / LBS	3.528
B	1.813 Inch 46.05 Millimeter
Nominal Bolt Center to Center	5 Inch 127 Millimeter
Bolt Spacing Minimum	4.687 Inch 119.05Millimeter
Bolt Spacing Maximum	5.313 Inch 134.95Millimeter
D	2.012 Inch 51.105 Millimeter
d	1.25 Inch 31.75 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bore diameter:	1.2500 in
overall width:	27 mm
bore type:	Round
radial dynamic load capacity:	5740 lbf
base to bore centerline:	1.8125 in
radial static load capacity:	3440 lbf
duty type:	Normal Duty
base width:	45 mm
housing material:	Cast Iron
bolt center-to-center length:	126 mm



NTN BEARING USA CORP.

locking device:	Eccentric Collar
maximum rpm:	5300 RPM
seal type:	Contact/Lip
lubrication type:	Lubrication Fitting
expansion type:	Non-Expansion Bearing (Fixed)
series:	SYH
overall length:	160 mm
replacement bearing:	YEL 207-104-2F
overall height:	91.5 mm
standards met:	ISO